






# BOARD TO BOARD FEMALE 0.5mm H=3.3mm

## SPECIFICATION

Current Rate:0.5 AMP  
 Insulation Resistance:100MΩ Min  
 Contact Resistance:30mΩ Max  
 Dielectric voltage:50V AC for one minute  
 Operation Temperature:-20°C to + 105°C

## MATERIAL


Insulator:Polyester,UL 94V-0  
 ◎Standard:Nylon 46  
 Contact Pin:Phosphor Bronze  
 Contact Plated:Gold Plated



◎After Mating Height


MATING HEIGHT	MALE P/N	FEMALE P/N
4.00	BTB05MK20-XX	BTB05FK33-XX

CIRCUITS	DIMENSION							
	A	B	C	D	E	F	G	H
20	10.00	6.75	5.50	4.50	7.00	9.80	10.40	7.60
26	11.50	8.25	7.00	6.00	8.50	11.30	11.90	9.10
30	12.50	9.25	8.00	7.00	9.50	12.30	12.90	10.10
40	15.00	11.75	10.50	9.50	12.00	14.80	15.40	12.60
50	17.50	14.25	13.00	12.00	14.50	17.30	17.90	15.10
60	20.00	16.75	15.50	14.50	17.00	19.80	20.40	17.60
70	22.50	19.25	18.00	17.00	19.50	22.30	22.90	20.10
80	25.00	21.75	20.50	19.50	22.00	24.80	25.40	22.60



Recommended PCB Layout  
 (PCB TOLERANCE ±0.05)

## ORDER INFORMATION



◎:Standard Recommend